

Small footprint  
monochrome terminal

Mounts anywhere

Perfect for point-of-sale/  
service



#### **SMALL IN SIZE**

The page-white monochrome 4000/260lf small footprint video display terminal occupies less than half the space required by standard 14" terminals. For customer transaction environments like retail counters, bank teller windows, hotels and rental car counters, the 4000/260lf delivers maximum productivity within a minimum space.

#### **BIG ON COMPATIBILITY**

No matter which operating environment you're working in, the 4000/260lf will be right at home. It is fully compatible with SCO®, UNIX® V.4, XENIX, PICK®, Multiuser DOS and many other operating environments.

#### **BIG ON CONNECTIVITY**

The 4000/260lf offers additional serial and parallel communications ports to support printers, cash drawers, customer display poles and more. An industry-standard mini-DIN keyboard interface supports wedge-type input devices such as bar code scanners and magnetic stripe readers.

#### **SAVE MONEY TODAY AND TOMORROW**

The 4000/260lf was designed to deliver the lowest cost of ownership in its class:

- Low acquisition costs enable you to stay within budget
- High reliability virtually eliminates downtime
- Extended warranty reduces maintenance and support costs

- User-friendly features increase operator efficiency and productivity
- Standard keyboards and VGA monitors protect your investment for the future

#### **ETHERNET CONNECTIVITY**

Users have the optional ability to access a single telnet session with their ADDS text terminal via our Ethernet Interface Adapter. It's a cost-effective alternative to using a PC to access text-based applications. It also helps protect your investment in terminals as your applications change.

#### **BUILT TO SUIT**

Boundless Technologies' "Just in Time" manufacturing techniques allow on-time delivery of any lot size in any configuration. You can select the small footprint terminal of your choice, with options of keyboards and customized logos or firmware. Whether you choose a standard or customized terminal, your order can be shipped quickly.

#### **BUILT TO LAST**

The ADDS 4000/260lf video display terminal is designed and manufactured in Boundless Technologies' ISO 9002-certified manufacturing plant in the U.S.A. Boundless backs its ADDS product line with optional extended warranties for smooth operation year after year.

**SPECIFICATIONS**

**ERGONOMICS**

9" monochrome terminal  
(approximate diagonal length  
of tube)  
Flexible, easy mounting

**DISPLAY FEATURES**

Flicker-free 70Hz refresh rate  
26, 44 or 49 lines with top  
and/or bottom status lines  
80 or 132 columns  
10 pages of memory  
2 pages of display, full- or  
split-screen viewing  
Selectable scrolling region  
Variable-speed smooth scroll  
Double-wide, double-high, and  
double-high/wide characters  
Selectable screen saver  
Programmable tab stops

**EMULATIONS**

SCO Console  
Wyse WY-60, WY-50/50+  
DEC VT-320, VT-220, VT-100  
TeleVideo TVI-925  
ADDS Viewpoint  
PCTerm (925 PC)  
AT 386 (UNIX® Console)

**COMPATIBILITY**

SCO, UNIX V.4, XENIX,  
PICK, Multiuser DOS and  
many other operating systems  
Most PC extender products

**DUAL-HOST SUPPORT**

Simultaneous connection and  
operation with two hosts  
Flexible display formats: 26-line  
alternating or 44-line split-  
screen  
"Hot key" to alternate  
between hosts  
Printer port support for  
both hosts

**ADDITIONAL FEATURES**

IBM® PC character set includes  
standard ASCII, line drawing,  
national symbols and special  
graphics symbols  
Desk accessories—calculator,  
calendar, clock, ASCII chart

**KEYBOARDS**

PC 101-key U.S. English key-  
board  
Available with PC+ 106-key or  
ANSI (VT-220 style) keyboards  
International PC 101/102,  
PC+ 106/107, and ANSI key-  
board layouts available  
Programmable function keys  
– 12/24 PFKs for PC 101/102  
– 16/32 PFKs for PC+106/107  
– 20/40 PFKs for ANSI  
(VT-220 style)  
PC 101, compact style  
(U.S. English only)  
PC 101, compact style, with  
integrated magnetic stripe  
reader (U.S. English only)



(Not to scale)

**LANGUAGES/  
CHARACTER SETS**

National or 8-bit PC mapping  
30 international language  
keyboards and character sets:  
Belgian/Flemish, Bosnian,  
Croatian, Czech, Danish,  
Dutch, Finnish, French,  
French Canadian, German,  
Greek, Hebrew, Hungarian,  
Italian, Latin American,  
Norwegian, Polish, Portuguese,  
Romanian, Russian,  
Serbian/Latin, Slovakian,  
Spanish, Swedish, Swiss/French,  
Swiss/German, Turkish, U.K.  
English, U.S. English

**COMMUNICATIONS**

Full/half duplex, local, block  
and monitor modes of  
operation  
Serial host port (EIA)  
– RS-232C, main host  
– DTE, DB-25 female or  
RJ-45 female  
– Up to 115.2K baud  
Serial auxiliary port (AUX)  
– RS-232C second host/serial  
port  
– DCE, RJ-45 female  
– Up to 38.4K baud  
Parallel printer port (Parallel)  
– Parallel printer/cash  
drawer/parallel  
output device  
– IBM PC cable and  
Centronics®-compatible

**OPTIONS**

RS-422, current loop  
Monochrome to color  
upgrade kit  
Ethernet (TCP/IP) Interface  
Adapter-10BaseT

**ENVIRONMENTAL**

Operating environment  
– Temperature: 50° to 104°F  
(10° to 40°C)  
– Altitude: 0 to 20,000 ft  
(0 to 6,096 m)  
– Humidity: 30 to 80% RH,  
non-condensing  
Storage environment  
– Temperature: 32° to 122°F  
(0° to 50°C)  
– Humidity: 10 to 95% RH,  
non-condensing

**POWER REQUIREMENTS**

Voltage: 110/220 VAC  
Frequency: 47/63Hz  
Current: 0.5/0.2 amps  
EPA ENERGY STAR® "Sleep  
Mode" (monitor dependent)

**PHYSICAL CHARACTERISTICS**

*Complete Unit*  
Length: 10.1" 25.6 cm  
Width: 9.75" 24.8 cm  
Height: 10.7" 27.3 cm  
Shipping wt.: 24.0 lbs 10.9 kg

**CERTIFICATIONS**

UL 1950  
CSA Standard 22.2, No. 950  
EN60950  
FCC Class A  
EN 55022 Class B  
EPA ENERGY STAR®  
(controller)  
CE Mark

**NEW YORK**

100 Marcus Boulevard  
Hauppauge, NY 11788-3762  
516.342.7400  
800.231.5445  
FAX 516.342.7378  
<http://www.boundless.com>

**AUSTIN**

Echelon IV, Suite 200  
9430 Research Boulevard  
Austin, TX 78759-6543  
512.349.5800  
FAX 512.346.7062

**EUROPE**

Den Bommel 2  
4194 TZ Meteren  
The Netherlands  
+31(0)345 56 56 56  
FAX +31(0)345 56 56 57

